

B.A.R.C.

BITUMEN & ASPHALT REMOVER/CLEANER

EASY TO USE

TREBLEX BARC'S best results have been achieved once dust and mud have been removed and the surface allowed to dry. Then:

- 1) Apply BARC with a hand held pressure sprayer and allow to penetrate for 15 to 20 minutes.
- 2) Rinse off with high pressure spray preferably using hot water.
- 3) Heavily encrusted areas may need a second application to allow BARC to penetrate fully.

Sizes available: 5L, 20L, 200L, 1000L

PRODUCT APPLICATIONS

Formulated specifically to remove Bitumen and Asphalt.

To be used on all equipment associated with the application of bitumen and asphalt.

Also removes bitumen from concrete, paving's, kerbs and brick.

Workshop floors and bench tops. Can be used for coating as well as cleaning equipment.

WHY>>>

Costs less than kerosene or diesel when used as directed

Multiple uses

Heavy industrial to home use

Environmentally responsible

Non- hazardous

Powerful

Plant derived bitumen remover

Coats as well as cleans

Safe and easy to use

Odourless, Non-Flammable



SAFETY

Keep out of reach of children. Read Material Safety Data Sheet before use.

PRODUCT CODE: TBARC

© Treblex Industrial Pty Ltd

TREBLEX®