

Product Name: Polycraft Contact Cleaner

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product Identifier

Product Name: Polycraft Contact Cleaner
Synonym(s):

1.2 Uses and uses advised against

Use(s) Cleaner for Contact Points

1.3 Details of the supplier of the product

Supplier Name TREBLEX INDUSTRIAL PTY LTD
Address U 1/26 Ilda Rd, CANNING VALE WA 6155
Telephone (08) 9456 5825
Fax (08) 9456 5875
Email sales@treblex.com.au
Website www.treblex.com.au

1.4 Emergency telephone number

Emergency 0438 120 976 AH / 08 9456 5825 Business hours

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

GHS Classification(s) Aerosols: Category 1
Skin Corrosion/Irritation: Category 2
Specific Target Organ Systemic Toxicity (Single Exposure): Category 3
Aquatic Toxicity (Chronic): Category 1

2.2 Label elements

Signal word DANGER

Pictogram(s)



Hazard statement(s)

H222 Extremely flammable aerosol
H229 Pressurised container: may burst if heated
H315 Causes skin irritation
H336 May cause drowsiness or dizziness
H410 Very toxic to aquatic life with long lasting effects.

Prevention statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
P211 Do not spray on an open flame or other ignition source
P251 Pressurised container: Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection

Response statement(s)

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTRE or doctor/physician if you feel unwell.

P321 Specific treatment is advised – see first aid instructions.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before re-use.
P391 Collect spillage.

Storage statement(s)

P403 + P233 Store in a well ventilated place. Keep container tightly closed
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Disposal statement(s)

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

No information provided.

3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

| Ingredient | CAS Number | EC Number | Content |
|------------|------------|-----------|---------|
| N-HEPTANE | 142-82-5 | 205-562-2 | <60% |
| BUTANE | 106-97-8 | 203-448-7 | <30% |
| PROPANE | 74-98-6 | 200-827-9 | <30% |

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic Vapour) respirator or and Air-line respirator (in poorly ventilated areas. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.

First aid facilities No information provided.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed.

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Highly flammable aerosol. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Aerosol may explode at temperatures exceeding 50°C. Eliminate all ignition sources, including cigarettes, open flames, spark producing switches/tools, heaters pilot lights, mobile phones, etc when handling. Aerosol cans may explode above 50°C.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

2YE
2 Fine Water Spray
Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.
E Evacuation of people in and around the immediate vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover/absorb spill with non-combustible absorbent material (vermiculite, sand or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool (<50°C), dry, well ventilated area, removed from incompatible substances and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/leaking containers. Large storage areas should have appropriate fire protection systems.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

| Ingredient | Reference | TWA | | STEL | |
|------------|-----------|------------|-------------------|------|-------------------|
| | | ppm | mg/m ³ | ppm | mg/m ³ |
| Butane | SWA (AUS) | 800 | 1900 | - | - |
| Propane | SWA (AUS) | Asphyxiant | | | |
| n-Heptane | SWA (AUS) | 400 | 1600 | 500 | 2050 |

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable vapours may accumulate in poorly ventilated or confined areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PPE

Eye / Face Hands Body Respiratory

Wear splash-proof goggles

Wear nitrile or neoprene gloves

When using large quantities or where heavy contamination is likely, wear coveralls.

At high vapour levels, wear a Type A-Class P1 (Organic gases/vapours and particulate) respirator.

Where the boiling point is <65°C, use an AX filter type.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| | |
|---------------------------|--|
| Appearance | PALE STRAW COLOURED LIQUID (AEROSOL DISPENSED) |
| Odour | SLIGHT ODOUR |
| Flammability | HIGHLY FLAMMABLE |
| Flash point | <23°C |
| Boiling point | NOT AVAILABLE |
| Melting point | NOT AVAILABLE |
| Evaporation rate | NOT AVAILABLE |
| pH | NOT AVAILABLE |
| Vapour density | NOT AVAILABLE |
| Specific gravity | 0.71 to 0.76 |
| Solubility (water) | INSOLUBLE |
| Vapour pressure | NOT AVAILABLE |
| Upper explosion limit | 9.5% (Propane) |
| Lower explosion limit | 2.2% (Propane) |
| Partition coefficient | NOT AVAILABLE |
| Autoignition temperature | NOT AVAILABLE |
| Decomposition temperature | NOT AVAILABLE |
| Viscosity | NOT AVAILABLE |
| Explosive properties | NOT AVAILABLE |
| Oxidising properties | NOT AVAILABLE |
| Odour threshold | NOT AVAILABLE |

9.2 Other Information

| | |
|-------------|------|
| % Volatiles | 100% |
|-------------|------|

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 incompatible materials

Incompatible with oxidising agents (eg-hypochlorites) and acids (eg-nitric acid)

10.6 hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Information available for the product:

Based on available data, the classification criteria are not met. This product may have the potential to cause adverse health effects if intentionally misused (eg-deliberately inhaling contents).

Information available for the ingredient(s):

| Ingredient | Oral Toxicity (LD50) | Dermal Toxicity (LD50) | Inhalation Toxicity (LC50) |
|------------|----------------------|------------------------|------------------------------------|
| N-HEPTANE | - | - | 103 g/m ³ hours (rat) |
| BUTANE | - | - | 658000 mg/m ³ /4H (rat) |
| PROPANE | - | - | > 800000 ppm/15M (rat) |

| | |
|---------------------------------|---|
| Skin | Contact may result in drying and defatting of the skin, rash and dermatitis. |
| Eye | Contact may result in irritation, lacrimation, pain and redness. |
| Sensitisation | Not classified as causing skin or respiratory sensitisation. |
| Mutagenicity | Not classified as a mutagen. |
| Carcinogenicity | Not classified as a carcinogen. |
| Reproductive | Not classified as a reproductive toxin. |
| STOT – single exposure | Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposure may result in nausea, dizziness and drowsiness. |
| STOT – repeated exposure | Not classified as causing organ damage from repeated exposure. |
| Aspiration | Not classified as causing aspiration. |

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2 persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small amounts, absorb contents with sand or similar and dispose of to an approved landfill site. Do not puncture or incinerate aerosol cans. Contact the manufacturer for additional information (if required).

Legislation Dispose of in accordance with local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



| | LAND TRANSPORT (ADG) | SEA TRANSPORT (IMDG / IMO) | AIR TRANSPORT (IATA / ICAO) |
|------------------------------------|----------------------|----------------------------|-----------------------------|
| 14.1 UN Number | 1950 | 1950 | 1950 |
| 14.2 Proper Shipping Name | AEROSOLS | AEROSOLS | AEROSOLS |
| 14.3 Transport Hazard Class | 2.1 | 2.1 | 2.1 |
| 14.4 Packing Group | None Allocated | None Allocated | None Allocated |

14.5 Environmental hazards Marine Pollutant

14.6 Special precautions for user

| | |
|---------------------|----------|
| Hazchem code | 2YE |
| GTEPG | 2D1 |
| EMS | F-D, S-U |

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|-----------------------------|--|
| Poison schedule | A poison schedule number has not been allocated to the product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). |
| Classifications | Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals. The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)] |
| Hazard codes | F+ Extremely flammable N Dangerous for the environment Xi Irritant Xn Harmful |
| Risk phrases | R12 Extremely flammable R38 Irritating to the skin R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67 Vapours may cause drowsiness and dizziness. |
| Safety phrases | S2 Keep out of reach of children S9 Keep container in a well ventilated place S16 Keep away from sources of ignition – No Smoking S29 Do not empty into drains. S33 Take precautionary measures against static discharges. S36/37 Wear suitable protective clothing and gloves. |
| Inventory listing(s) | AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt. |

16. OTHER INFORMATION

Additional Information

AEROSOL CANS may explode at temperatures approaching 50°C.

RESPIRATORS: In general, the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn, ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

| | | |
|---------------|-------------------|--|
| Abbreviations | ACGIH | American Conference of Governmental Industrial Hygienists |
| | CAS # | Chemical Abstract Service Number-used to uniquely identify chemical compounds |
| | CNS | Central Nervous System |
| | EC No. | EC No – European Community Number |
| | EMS | Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) |
| | GHS | Globally Harmonized System |
| | GTEPG | Group Text Emergency Procedure Guide |
| | IARC | International Agency for Research on Cancer |
| | LC50 | Lethal Concentration, 50% / Median Lethal Concentration |
| | LD50 | Lethal Dose, 50% / Medial Lethal Dose |
| | Mg/m ³ | Milligrams per Cubic Metre |
| | OEL | Occupational Exposure Limit |
| | pH | Relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline) |
| | ppm | Parts Per Million |



Solutions for Industry

SAFETY DATA SHEET

| | |
|---------|--|
| STEL | Short-Term Exposure Limit |
| STOT-RE | Specific target organ toxicity (repeated exposure) |
| STOT-SE | Specific target organ toxicity (single exposure) |
| SUSMP | Standard for the Uniform Scheduling of Medicines and Poisons |
| SWA | Safe Work Australia |
| TLV | Threshold Limit Value |
| TWA | Time Weighted Average |

| | |
|---------------------------|-------------------|
| Date Of Preparation: | 01 September 2016 |
| Revision Number: | 2 |
| Changes in this revision: | Initial Document |
| Prepared By: | VM |

This MSDS summarises product safety information at the date of issue, to the best of our knowledge, as a general guide. Treblex Industrial Pty Ltd cannot anticipate or control the conditions under which the product is used, so prior to usage each user must assess and control the risks associated with their use of this product. Users should also consult the relevant legislation governing the use and storage of this product. We make no warranties, expressed or implied, and assume no liability in connection with any use of information contained within this document. If clarification or further information is needed, the user should contact Treblex Industrial Pty Ltd.