



Solutions for Industry

SAFETY DATA SHEET

Product Name **Wire Rope Lube Oil**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name TREBLEX INDUSTRIAL PTY LTD
Address U1/26 ilda Road,Canning Vale WA, AUSTRALIA, 6155
Telephone (08) 9456 5825
Fax (08) 9456 5875
Emergency 0433 011 771
Web Site www.treblex.com.au

Use(s) WIRE ROP LUBRICANT • MOISTURE REPELLENT LUBRICANT • RUST PREVENTATIVE
SDS Date April 2019

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA
NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. None Allocated **DG Class** None Allocated **Subsidiary Risk(s)** None Allocated

Packing Group None Allocated **Hazchem Code** None Allocated **EPG** None Allocated

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
MINERAL OIL (SOLVENT REFINED)	Not Available	Not Available	>80%
ADDITIVE(S)	Not Available	Not Available	<20%

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

Advice to Doctor Treat symptomatically

5. FIRE FIGHTING MEASURES

Flammability Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

Fire and Explosion Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Extinguishing Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.

Hazchem Code None Allocated

